

# Package: wsMed (via r-universe)

September 18, 2026

**Title** Within-Subject Mediation Analysis Using Structural Equation Modeling

**Version** 1.1.0

**Description** Within-subject mediation analysis using structural equation modeling. Examine how changes in an outcome variable between two conditions are mediated through one or more variables. Supports within-subject mediation analysis using the 'lavaan' package by Rosseel (2012) <[doi:10.18637/jss.v048.i02](https://doi.org/10.18637/jss.v048.i02)>, and extends Monte Carlo confidence interval estimation to missing data scenarios using the 'semmcci' package by Pesigan and Cheung (2023) <[doi:10.3758/s13428-023-02114-4](https://doi.org/10.3758/s13428-023-02114-4)>.

**License** GPL (>= 3)

**Depends** R (>= 4.1.0)

**Encoding** UTF-8

**RoxygenNote** 7.3.3

**Suggests** rmarkdown, devtools, testthat

**Config/testthat/edition** 3

**Imports** knitr, lavaan, semmcci, mice, semboottools, MASS, rlang, dplyr, ggplot2, methods, stats

**VignetteBuilder** knitr

**LazyData** true

**URL** <https://yangzhen1999.github.io/wsMed/>

**BugReports** <https://github.com/Yangzhen1999/wsMed/issues>

**NeedsCompilation** no

**Author** Wendie Yang [aut, cre] (ORCID: <<https://orcid.org/0009-0000-8388-6481>>), Shu Fai Cheung [aut] (ORCID: <<https://orcid.org/0000-0002-9871-9448>>)

**Maintainer** Wendie Yang <1581075494q@gmail.com>

**Config/pak/sysreqs** cmake make libicu-dev libssl-dev libx11-dev zlib1g-dev

**Repository** <https://yangzhen1999.r-universe.dev>

**Date/Publication** 2026-09-18 03:14:31 UTC  
**RemoteUrl** https://github.com/yangzhen1999/wsmed  
**RemoteRef** HEAD  
**RemoteSha** 2cec48839af9b393704cb0fcab40cc9e8e9f9a71

Contents

|                                    |           |
|------------------------------------|-----------|
| GenerateModelCN . . . . .          | 2         |
| GenerateModelCP . . . . .          | 4         |
| GenerateModelCustom . . . . .      | 6         |
| GenerateModelIP . . . . .          | 7         |
| GenerateModelPC . . . . .          | 8         |
| ImputeData . . . . .               | 10        |
| MCMi2 . . . . .                    | 11        |
| plot_conditional_effects . . . . . | 13        |
| plot_contrasts . . . . .           | 15        |
| plot_effects . . . . .             | 16        |
| plot_moderation_curve . . . . .    | 18        |
| PrepareData . . . . .              | 19        |
| PrepareMissingData . . . . .       | 21        |
| print.wsMed . . . . .              | 24        |
| printGM . . . . .                  | 25        |
| standardize_moderation . . . . .   | 26        |
| wsMed . . . . .                    | 27        |
| <b>Index</b>                       | <b>31</b> |

---

|                 |                                         |
|-----------------|-----------------------------------------|
| GenerateModelCN | <i>Generate Chained Mediation Model</i> |
|-----------------|-----------------------------------------|

---

Description

Dynamically generates a structural equation modeling (SEM) syntax for chained mediation analysis based on the prepared dataset. The function computes regression equations for mediators and the outcome variable, indirect effects along multi-step mediation paths, total effects, contrasts between indirect effects, and coefficients in different conditions.

Usage

```
GenerateModelCN(prepared_data, MP = character(0))
```

## Arguments

- `prepared_data` A data frame returned by [PrepareData\(\)](#), containing the processed within-subject mediator and outcome variables. The data frame must include columns for difference scores (`Mdiff`) and average scores (`Mavg`) of mediators, as well as the outcome difference score (`Ydiff`).
- `MP` A character vector specifying which paths are moderated by variable(s) `W`. Valid entries include: - `"a2"`, `"a3"`, ...: moderation on the a paths ( $W \rightarrow Mdiff$ ), for mediators beyond `M1`. - `"b2"`, `"b3"`, ...: moderation on the b paths ( $Mdiff \times W \rightarrow Ydiff$ ). - `"b_1_2"`, `"b_2_3"`, ...: moderation on cross-paths from one mediator to the next (e.g.,  $M1 \rightarrow M2$ ). - `"d2"`, `"d3"`, ...: moderation on the d paths ( $Mavg \times W \rightarrow Ydiff$ ). - `"d_1_2"`, `"d_2_3"`, ...: moderation on cross-paths from one `Mavg` to the next `Mdiff`. - `"cp"`: moderation on the direct effect from `X` to `Y` (i.e.,  $W \rightarrow Ydiff$ ).

The function detects and inserts the correct interaction terms (e.g., `\code{int_M2d`

## Details

This function is used to construct SEM models for chained mediation analysis. It automatically parses variable names from the prepared dataset and dynamically creates the necessary model syntax, including:

- **Outcome regression:** Defines the relationship between the difference scores of the outcome (`Ydiff`) and the mediators (`Mdiff`) as well as their average scores (`Mavg`).
- **Mediator regressions:** Defines the sequential regression models for each mediator's difference score, incorporating prior mediators as predictors.
- **Indirect effects:** Computes the indirect effects along all possible multi-step mediation paths using the product of path coefficients.
- **Total indirect effect:** Calculates the sum of all indirect effects from the chained mediation paths.
- **Total effect:** Combines the direct effect (`cp`) and the total indirect effect.
- **Contrasts of indirect effects:** Optionally calculates the pairwise contrasts between the indirect effects for different mediation paths.
- **Coefficients in different 'X' conditions:** Calculates path coefficients in different `X` conditions to observe the moderation effect of `X`.

This model is suitable for chained mediation designs where mediators influence each other in a sequential manner, forming multi-step mediation paths.

## Value

A character string representing the SEM model syntax for the specified chained mediation analysis.

## See Also

[PrepareData\(\)](#), [wsMed\(\)](#), [GenerateModelP\(\)](#)

## Examples

```
# Example prepared data
prepared_data <- data.frame(
  M1diff = rnorm(100),
  M2diff = rnorm(100),
  M3diff = rnorm(100),
  M1avg = rnorm(100),
  M2avg = rnorm(100),
  M3avg = rnorm(100),
  Ydiff = rnorm(100)
)

# Generate SEM model syntax
sem_model <- GenerateModelCN(prepared_data)
cat(sem_model)
```

---

GenerateModelCP

*Generate Combined Parallel and Chained Mediation Model*

---

## Description

Dynamically generates a structural equation modeling (SEM) syntax for combined parallel and chained mediation analysis based on the prepared dataset. The function computes regression equations for mediators and the outcome variable, indirect effects for both parallel and chained mediation paths, total effects, contrasts between indirect effects, and coefficients in different X conditions.

## Usage

```
GenerateModelCP(prepared_data, MP = character(0))
```

## Arguments

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| prepared_data | A data frame returned by <a href="#">PrepareData()</a> , containing the processed within-subject mediator and outcome variables. The data frame must include columns for difference scores (Mdiff) and average scores (Mavg) of mediators, as well as the outcome difference score (Ydiff).                                                                                                                                                                                                                                                                                                              |
| MP            | A character vector specifying which paths are moderated by variable(s) W. Acceptable values include: - "a2", "a3", ...: moderation on the a paths of parallel mediators ( $W \rightarrow Mdiff$ ). - "b2", "b3", ...: moderation on the b paths of parallel mediators ( $Mdiff \times W \rightarrow Ydiff$ ). - "b_1_2", "b_1_3", ...: moderation on the paths from the chain mediator to parallel mediators. - "d_1_2", "d_1_3", ...: moderation on the paths from the chain mediator's Mavg to parallel mediators. - "cp": moderation on the direct effect from X to Y (i.e., $W \rightarrow Ydiff$ ). |

Each entry triggers inclusion of W's main effect or interaction terms (e.g., `\code{W}`).

## Details

This function is used to construct SEM models that combine parallel and chained mediation analysis. It automatically parses variable names from the prepared dataset and dynamically creates the necessary model syntax, including:

- **Outcome regression:** Defines the relationship between the difference scores of the outcome (*Ydiff*), the chained mediator (*M1diff*), and the parallel mediators (*M2diff*, *M3diff*, etc.).
- **Mediator regressions:** Defines the sequential regression models for the chained mediator and each parallel mediator.
- **Indirect effects:** Computes the indirect effects for both chained and parallel mediation paths, including multi-step indirect effects involving both chained and parallel mediators.
- **Total indirect effect:** Calculates the sum of all indirect effects from chained and parallel mediation paths.
- **Total effect:** Combines the direct effect (*cp*) and the total indirect effect.
- **Contrasts of indirect effects:** Optionally calculates the pairwise contrasts between the indirect effects for different mediation paths.
- **Coefficients in different 'X' conditions:** Calculates path coefficients in different X conditions to observe the moderation effect of X.

This model is suitable for designs where mediators include both a sequential chain (chained mediation) and independent parallel mediators.

## Value

A character string representing the SEM model syntax for the specified combined parallel and chained mediation analysis.

## See Also

[PrepareData\(\)](#), [wsMed\(\)](#), [GenerateModelP\(\)](#), [GenerateModelCN\(\)](#)

## Examples

```
# Example prepared data
prepared_data <- data.frame(
  M1diff = rnorm(100),
  M2diff = rnorm(100),
  M3diff = rnorm(100),
  M1avg = rnorm(100),
  M2avg = rnorm(100),
  M3avg = rnorm(100),
  Ydiff = rnorm(100)
)

# Generate SEM model syntax
sem_model <- GenerateModelCP(prepared_data)
cat(sem_model)
```

---

|                     |                                                               |
|---------------------|---------------------------------------------------------------|
| GenerateModelCustom | <i>Generate a User-Defined Within-Subject Mediation Model</i> |
|---------------------|---------------------------------------------------------------|

---

## Description

Generates lavaan model syntax for a user-defined within-subject mediation model. Users specify directed paths among mediators and from mediators to the outcome. The function automatically adds the corresponding difference and level components and identifies all indirect effects.

## Usage

```
GenerateModelCustom(prepared_data, paths, MP = character(0))
```

## Arguments

|               |                                                                                                                                                                                                                                                                                                  |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| prepared_data | A data frame returned by [PrepareData()]. It must contain ‘M1diff’, ‘M1avg’, ..., and ‘Ydiff’.                                                                                                                                                                                                   |
| paths         | A character vector defining directed paths among mediators and from mediators to the outcome. For example: ‘c("M1 -> M2", "M2 -> Y")’.                                                                                                                                                           |
| MP            | <p>A character vector identifying moderated paths. Supported labels follow the existing wsMed convention: ‘a1’, ‘b1’, ‘d1’, ‘b_1_2’, ‘d_1_2’, and ‘cp’.</p> <p>Main effects of W are always labeled and used for conditional intercepts, including when a/cp is not explicitly listed in MP.</p> |

## Value

A character string containing lavaan model syntax.

## Examples

```
prepared_data <- data.frame(
  M1diff = rnorm(100),
  M1avg  = rnorm(100),
  M2diff = rnorm(100),
  M2avg  = rnorm(100),
  M3diff = rnorm(100),
  M3avg  = rnorm(100),
  Ydiff  = rnorm(100)
)

model <- GenerateModelCustom(
  prepared_data = prepared_data,
  paths = c(
    "M1 -> M3",
    "M1 -> Y",
    "M3 -> Y",
    "M2 -> Y"
  )
)
```

```
)
cat(model)
```

---

GenerateModelP

*Generate Parallel Mediation Model*


---

## Description

Dynamically generates a structural equation modeling (SEM) syntax for parallel mediation analysis based on the prepared dataset. The function computes regression equations for mediators and the outcome variable, indirect effects, total effects, contrasts between indirect effect, and .

## Usage

```
GenerateModelP(prepared_data, MP = character(0))
```

## Arguments

**prepared\_data** A data frame returned by [PrepareData\(\)](#), containing the processed within-subject mediator and outcome variables. The data frame must include columns for difference scores (Mdiff) and average scores (Mavg) of mediators, as well as the outcome difference score (Ydiff).

**MP** A character vector specifying which paths are moderated by variable(s) W. Valid values include: - "a1", "a2", ...: moderation on the a paths ( $W \rightarrow \text{Mdiff}$ ). - "b1", "b2", ...: moderation on the b paths ( $\text{Mdiff} \times W \rightarrow \text{Ydiff}$ ). - "d1", "d2", ...: moderation on the d paths ( $\text{Mavg} \times W \rightarrow \text{Ydiff}$ ). - "cp": moderation on the direct effect from X to Y (i.e.,  $W \rightarrow \text{Ydiff}$ ).

This argument controls which interaction terms (e.g., `int_Mdiff_W`, `int_Mdiff_W^2`, ...) are added to the corresponding regression equations.

## Details

This function is used to construct SEM models for parallel mediation analysis. It automatically parses variable names from the prepared dataset and dynamically creates the necessary model syntax, including:

- **Outcome regression:** Defines the relationship between the difference scores of the outcome (Ydiff) and the mediators (Mdiff) as well as their average scores (Mavg).
- **Mediator regressions:** Defines the intercept models for each mediator's difference score.
- **Indirect effects:** Computes the indirect effects for each mediator using the product of path coefficients (e.g.,  $a \times b$ ).
- **Total indirect effect:** Calculates the sum of all indirect effects.
- **Total effect:** Combines the direct effect (cp) and the total indirect effect.

- **Contrasts of indirect effects:** Optionally calculates the pairwise contrasts between the indirect effects when multiple mediators are present.
- **coefficients in different 'X' conditions:** Calculates path coefficients in different X conditions to observe the moderation effect of 'X'.

This model is suitable for parallel mediation designs where multiple mediators act independently.

### Value

A character string representing the SEM model syntax for the specified parallel mediation analysis.

### See Also

[PrepareData\(\)](#), [wsMed\(\)](#), [GenerateModelCN\(\)](#)

### Examples

```
# Example prepared data
prepared_data <- data.frame(
  M1diff = rnorm(100),
  M2diff = rnorm(100),
  M1avg = rnorm(100),
  M2avg = rnorm(100),
  Ydiff = rnorm(100)
)

# Generate SEM model syntax
sem_model <- GenerateModelP(prepared_data)
cat(sem_model)
```

---

GenerateModelPC

*Generate Parallel and Chained Mediation Model*

---

### Description

Dynamically generates a structural equation modeling (SEM) syntax for mediation analysis that integrates both parallel and chained mediators. Unlike the Combined Parallel and Chained mediation model (GenerateModelCP), this function assumes that the chained mediator receives inputs from the parallel mediators and directly influences the outcome variable, emphasizing a downstream role for the chained mediator.

### Usage

```
GenerateModelPC(prepared_data, MP = character(0))
```

## Arguments

- `prepared_data` A data frame returned by `PrepareData()`, containing the processed within-subject mediator and outcome variables. The data frame must include columns for difference scores (`Mdiff`) and average scores (`Mavg`) of mediators, as well as the outcome difference score (`Ydiff`).
- `MP` A character vector specifying which paths are moderated by variable(s) `W`. Acceptable values include: - `"a2"`, `"a3"`, ...: moderation on the a paths ( $W \rightarrow Mdiff$ ). - `"b2"`, `"b3"`, ...: moderation on the b paths ( $Mdiff \times W \rightarrow Ydiff$ ). - `"b_2_1"`, `"b_3_1"`, ...: moderation on the cross-paths from parallel mediators to the chain mediator (e.g.,  $M2 \rightarrow M1$ ). - `"d_2_1"`, `"d_3_1"`, ...: moderation on the paths from parallel mediators' centered means to `M1`. - `"cp"`: moderation on the direct effect of `X` on `Y` (i.e.,  $W \rightarrow Ydiff$ ).

This argument controls which interaction terms (e.g., `\code{int_Mdiff_W}`, `\code{int_Mdiff_W_M1}`) in the regression equations. Variable names are automatically matched using the name `\code{"int_<predictor>_W<index>"}`.

## Details

This function is designed to build SEM models that integrate parallel and chained mediation structures. It automatically identifies variable names from the prepared dataset and generates the necessary model syntax, including:

- **Outcome regression:** Defines the relationship between the difference scores of the outcome (`Ydiff`), the chained mediator (`M1diff`), and the parallel mediators (`M2diff`, `M3diff`, etc.).
- **Mediator regressions:** Constructs separate regression models for the parallel mediators and the chained mediator. The chained mediator incorporates predictors from all parallel mediators.
- **Indirect effects:** Computes indirect effects for:
  - Parallel mediators (`M2diff`, `M3diff`, etc.) directly influencing the outcome.
  - The chained mediator (`M1diff`) directly influencing the outcome.
  - Combined paths where parallel mediators influence the chained mediator, which in turn influences the outcome.
- **Total indirect effect:** Summarizes all indirect effects from parallel and chained mediation paths.
- **Total effect:** Combines the direct effect (`cp`) and the total indirect effect.
- **Contrasts of indirect effects:** Optionally computes pairwise contrasts between indirect effects for different mediation paths.
- **Coefficients in different 'X' conditions:** Computes path coefficients under different `X` conditions to analyze moderation effects.

This model is suitable for designs where mediators include both independent parallel paths and sequential chained paths, providing a comprehensive mediation analysis framework.

## Value

A character string representing the SEM model syntax for the specified parallel and chained mediation analysis.

**See Also**

[PrepareData\(\)](#), [wsMed\(\)](#), [GenerateModelP\(\)](#), [GenerateModelCN\(\)](#)

**Examples**

```
# Example prepared data
prepared_data <- data.frame(
  M1diff = rnorm(100),
  M2diff = rnorm(100),
  M3diff = rnorm(100),
  M1avg = rnorm(100),
  M2avg = rnorm(100),
  M3avg = rnorm(100),
  Ydiff = rnorm(100)
)

# Generate SEM model syntax
sem_model <- GenerateModelPC(prepared_data)
cat(sem_model)
```

---

ImputeData

---

*Impute Missing Data Using Multiple Imputation*


---

**Description**

The `ImputeData` function performs multiple imputation on a data frame with missing values using the `mice` package. It handles missing data by creating multiple imputed datasets based on a specified imputation method and returns a list of completed data frames.

**Usage**

```
ImputeData(
  data_missing,
  m = 5,
  method = "pmm",
  seed = 123,
  predictorMatrix = NULL
)
```

**Arguments**

|                           |                                                                                                                             |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| <code>data_missing</code> | A data frame containing missing values to be imputed. The function replaces values coded as -999 with NA before imputation. |
| <code>m</code>            | An integer specifying the number of imputed datasets to generate.                                                           |
| <code>method</code>       | A character string specifying the imputation method. Default is "pmm" (predictive mean matching).                           |

**seed** An integer for setting the random seed to ensure reproducibility. Default is 123.

**predictorMatrix** An optional matrix specifying the predictor structure for the imputation model. Default is NULL, meaning that the function will use the default predictor matrix created by mice.

### Details

This function replaces specified missing value placeholders (e.g., -999) with NA, and then applies the multiple imputation by chained equations (MICE) procedure to generate multiple imputed datasets. It supports flexible imputation methods and allows for specifying a custom predictor matrix.

### Value

A list of *m* imputed data frames.

### Author(s)

Wendie Yang, Shufai Cheung

### Examples

```
# Example data with missing values
data <- data.frame(
  M1 = c(rnorm(99), rep(NA, 1)),
  M2 = c(rnorm(99), rep(NA, 1)),
  Y1 = rnorm(100),
  Y2 = rnorm(100)
)
# Perform multiple imputation
imputed_data_list <- ImputeData(data, m = 5)
# Display the first imputed dataset
head(imputed_data_list[[1]])
```

### Description

Computes Monte Carlo confidence intervals (MCCI) for structural equation models (SEM) fitted to multiple imputed datasets. This function integrates SEM fitting across imputed datasets, pools the results, and generates confidence intervals through Monte Carlo sampling.

**Usage**

```
MCM12(
  sem_model,
  imputations,
  R = 20000L,
  alpha = c(0.001, 0.01, 0.05),
  decomposition = "eigen",
  pd = TRUE,
  tol = 1e-06,
  seed = NULL,
  estimator = "ML",
  se = "standard",
  missing = "listwise",
  fixed.x = FALSE
)
```

**Arguments**

|                            |                                                                                                                                                  |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>sem_model</code>     | A character string specifying the SEM model syntax.                                                                                              |
| <code>imputations</code>   | A list of data frames, where each data frame represents an imputed dataset.                                                                      |
| <code>R</code>             | An integer specifying the number of Monte Carlo samples. Default is '20000L'.                                                                    |
| <code>alpha</code>         | A numeric vector specifying significance levels for the confidence intervals. Default is 'c(0.001, 0.01, 0.05)'.                                 |
| <code>decomposition</code> | A character string specifying the decomposition method for the covariance matrix. Default is "eigen". Options include "chol", "eigen", or "svd". |
| <code>pd</code>            | A logical value indicating whether to ensure positive definiteness of the covariance matrix. Default is 'TRUE'.                                  |
| <code>tol</code>           | A numeric value specifying the tolerance for positive definiteness checks. Default is '1e-06'.                                                   |
| <code>seed</code>          | An optional integer specifying the random seed for reproducibility. Default is 'NULL'.                                                           |
| <code>estimator</code>     | A character string specifying the estimator for SEM fitting. Default is "ML" (Maximum Likelihood).                                               |
| <code>se</code>            | A character string specifying the type of standard errors to compute. Default is "standard".                                                     |
| <code>missing</code>       | A character string specifying the method for handling missing data in SEM fitting. Default is "listwise".                                        |
| <code>fixed.x</code>       | Whether exogenous covariates are treated as fixed in every imputation. Defaults to FALSE, consistently with <code>wsMed()</code> .               |

**Details**

This function is designed for SEM models that require multiple imputation to handle missing data. It performs the following steps:

- **SEM Fitting**: Fits the specified SEM model to each imputed dataset using `[lavaan::sem()]`.

- **\*\*Pooling Results\*\***: Combines parameter estimates and covariance matrices across imputations using Rubin's rules.

- **\*\*Monte Carlo Sampling\*\***: Generates Monte Carlo samples based on the pooled estimates and covariance matrices, and calculates confidence intervals for model parameters.

This function supports custom estimators, handling of missing data, and precision adjustments for Monte Carlo sampling. It is particularly useful for mediation analysis or complex SEM models where missing data are addressed using multiple imputation.

### Value

An object of class 'semmcci' containing: - 'call': The matched function call. - 'args': A list of input arguments. - 'thetahat': The pooled parameter estimates. - 'thetahatstar': Monte Carlo samples for parameter estimates. - 'fun': The name of the function ("MCMi2").

### See Also

[lavaan::sem()], [semmcci::MC()], [semmcci::MCStd()]

### Examples

```
# Example SEM model
sem_model <- "
  Ydiff ~ b1 * M1diff + cp * 1
  M1diff ~ a1 * 1
  indirect := a1 * b1
  total := cp + indirect
"

# Example imputed datasets
imputations <- list(
  data.frame(M1diff = rnorm(100), Ydiff = rnorm(100)),
  data.frame(M1diff = rnorm(100), Ydiff = rnorm(100))
)

# Compute Monte Carlo confidence intervals
result <- MCMi2(
  sem_model = sem_model,
  imputations = imputations,
  R = 1000,
  alpha = c(0.05, 0.01),
  seed = 123
)
```

## Description

Draw point estimates and confidence intervals by categorical group or by the stored low, mean and high levels of a continuous moderator. Each effect is shown in its own panel. Categories are not joined by interpolating lines.

## Usage

```
plot_conditional_effects(
  result,
  paths = NULL,
  type = c("indirect", "paths", "overall"),
  levels = NULL,
  standardized = FALSE,
  engine = c("mc", "boot"),
  labels = NULL,
  title = NULL,
  x_label = NULL,
  y_label = NULL,
  base_size = 12,
  ncol = NULL
)
```

## Arguments

|                  |                                                                                                                                                                                                    |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| result           | A result returned by <a href="#">wsMed()</a> .                                                                                                                                                     |
| paths            | Optional character vector of effect identifiers, in display order. NULL selects all available effects. Both indirect_1 and indirect_effect_1 are accepted when they identify an available effect.  |
| type             | "indirect" for specific indirect effects, "paths" for available conditional path coefficients, or "overall" for total indirect and total effects.                                                  |
| levels           | Optional group/level labels to select, in display order. NULL uses their stored order. For continuous W the labels are "-1 SD", "0 SD", "+1 SD"; the axis also displays stored raw W probe values. |
| standardized     | Use standardized results, requested when fitting with standardized = TRUE. No scaling is recomputed from interval endpoints.                                                                       |
| engine           | For ci_method = "both", select "mc" or "boot". For a single engine its stored results are used.                                                                                                    |
| labels           | Optional named character vector mapping effect identifiers to display labels. Partial mappings are allowed.                                                                                        |
| title            | Optional plot title.                                                                                                                                                                               |
| x_label, y_label | Optional axis labels.                                                                                                                                                                              |
| base_size        | Base font size.                                                                                                                                                                                    |
| ncol             | Optional number of facet columns.                                                                                                                                                                  |

**Details**

Intervals are the stored percentile conditional intervals, including jointly transformed scales for standardized results. They are individual intervals, not simultaneous confidence intervals.

**Value**

A ggplot object with plotted data and a `wsmed_plot` attribute.

**See Also**

[plot\\_effects\(\)](#), [plot\\_contrasts\(\)](#)

---

|                |                                                   |
|----------------|---------------------------------------------------|
| plot_contrasts | <i>Plot differences between mediation effects</i> |
|----------------|---------------------------------------------------|

---

**Description**

Draw contrast estimates and their confidence intervals relative to zero. With a moderator, contrasts compare groups or stored moderator levels within each effect. Without a moderator, specific indirect paths are compared with one another. The displayed subtraction order is explicit.

**Usage**

```
plot_contrasts(
  result,
  paths = NULL,
  type = c("indirect", "paths", "overall"),
  contrasts = NULL,
  standardized = FALSE,
  engine = c("mc", "boot"),
  labels = NULL,
  title = NULL,
  x_label = NULL,
  y_label = NULL,
  base_size = 12,
  ncol = NULL
)
```

**Arguments**

|                     |                                                                                                                                                                                                                             |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>result</code> | A result returned by <a href="#">wsMed()</a> .                                                                                                                                                                              |
| <code>paths</code>  | Optional character vector of effect identifiers, in display order. NULL selects all available effects. Both <code>indirect_1</code> and <code>indirect_effect_1</code> are accepted when they identify an available effect. |
| <code>type</code>   | "indirect" for specific indirect effects, "paths" for available conditional path coefficients, or "overall" for total indirect and total effects.                                                                           |

|                  |                                                                                                                                                                                  |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| contrasts        | Optional exact contrast labels to select, in display order. NULL selects all. Inspect the corresponding result table or the returned plot's data\$Contrast for available labels. |
| standardized     | Use standardized results, requested when fitting with standardized = TRUE. No scaling is recomputed from interval endpoints.                                                     |
| engine           | For ci_method = "both", select "mc" or "boot". For a single engine its stored results are used.                                                                                  |
| labels           | Optional named character vector mapping effect identifiers to display labels. Partial mappings are allowed.                                                                      |
| title            | Optional plot title.                                                                                                                                                             |
| x_label, y_label | Optional axis labels.                                                                                                                                                            |
| base_size        | Base font size.                                                                                                                                                                  |
| ncol             | Optional number of facet columns.                                                                                                                                                |

Details

Moderator contrasts use the existing joint-draw contrast tables. Without a moderator, only type = "indirect" is available: contrasts are computed from the stored joint draws, with point estimates evaluated at fitted/pooled parameters. Their intervals are percentile intervals. Standardized draws use the same draw-specific marginal endpoint scales as other standardized effects. No model is refitted. Interval endpoints for two separate effects are never subtracted to construct a contrast CI. paths and labels apply to effect panels when a moderator is present; without a moderator, paths selects the indirect effects to compare and labels maps the full contrast labels. Continuous overall contrasts are unavailable when the fitted result does not contain that contrast table.

Value

A ggplot object with plotted data and a wsmed\_plot attribute.

See Also

[plot\\_effects\(\)](#), [plot\\_conditional\\_effects\(\)](#)

---

|              |                                         |
|--------------|-----------------------------------------|
| plot_effects | <i>Forest plot of mediation effects</i> |
|--------------|-----------------------------------------|

---

Description

Plot fitted indirect effects, the total indirect effect, the direct effect (cp) and the total effect with their stored confidence intervals. With a moderator these are effects at the model's reference value (centered continuous  $W = 0$ , or the reference category), not averages across  $W$ . Use [plot\\_conditional\\_effects\(\)](#) to show selected moderator levels instead.

**Usage**

```
plot_effects(
  result,
  paths = NULL,
  standardized = FALSE,
  engine = c("mc", "boot"),
  labels = NULL,
  title = NULL,
  x_label = NULL,
  y_label = NULL,
  base_size = 12
)
```

**Arguments**

|                  |                                                                                                                                                                                                   |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| result           | A result returned by <a href="#">wsMed()</a> .                                                                                                                                                    |
| paths            | Optional character vector of effect identifiers, in display order. NULL selects all available effects. Both indirect_1 and indirect_effect_1 are accepted when they identify an available effect. |
| standardized     | Use standardized results, requested when fitting with standardized = TRUE. No scaling is recomputed from interval endpoints.                                                                      |
| engine           | For ci_method = "both", select "mc" or "boot". For a single engine its stored results are used.                                                                                                   |
| labels           | Optional named character vector mapping effect identifiers to display labels. Partial mappings are allowed.                                                                                       |
| title            | Optional plot title.                                                                                                                                                                              |
| x_label, y_label | Optional axis labels.                                                                                                                                                                             |
| base_size        | Base font size.                                                                                                                                                                                   |

**Details**

MC intervals come from the parameter draws (or the stored standardized parameter table). Bootstrap plots use the bootstrap limits, not the normal-theory limits that may also be present in the table.

**Value**

A ggplot object. Its data contains the plotted estimates and CI.LL/CI.UL limits. The wsmed\_plot attribute records the selected engine, scale and confidence level. Use [ggplot2::ggsave\(\)](#) to export it.

**See Also**

[plot\\_conditional\\_effects\(\)](#), [plot\\_contrasts\(\)](#), [plot\\_moderation\\_curve\(\)](#)

---

plot\_moderation\_curve *Plot conditional effects across a continuous moderator*

---

## Description

Plot a conditional indirect effect, total effect or path coefficient with its pointwise confidence band. Highlight stored grid values whose interval excludes zero. Boundary labels use raw moderator units, not sample percentiles.

## Usage

```
plot_moderation_curve(
  result,
  path_name,
  title = NULL,
  x_label = "Moderator (W, raw units)",
  y_label = "Estimate",
  ns_fill = "#FEE0D2",
  sig_fill = "#C7E9C0",
  alpha_ci = 0.35,
  alpha_sig = 0.35,
  base_size = 14,
  standardized = FALSE,
  engine = c("mc", "boot")
)
```

## Arguments

|                     |                                                                                                                                        |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| result              | A result returned by <code>wsMed()</code> with a continuous moderator.                                                                 |
| path_name           | One stored effect identifier, such as "indirect_effect_1_2", "total_indirect" or "b_1_2". "indirect_1_2" is also accepted as an alias. |
| title               | Optional plot title.                                                                                                                   |
| x_label, y_label    | Axis labels. The default x axis uses raw W units.                                                                                      |
| ns_fill             | Colour of the complete confidence band.                                                                                                |
| sig_fill            | Colour of the regions whose pointwise CI excludes zero.                                                                                |
| alpha_ci, alpha_sig | Opacity of the band and highlighted regions.                                                                                           |
| base_size           | Base font size.                                                                                                                        |
| standardized        | Use the stored standardized conditional results.                                                                                       |
| engine              | For ci_method = "both", select "mc" or "boot".                                                                                         |

### Details

Highlighted intervals are approximate ranges on the stored grid, not exact Johnson–Neyman boundaries or simultaneous confidence regions. A label [a, b] reports the first and last qualifying grid values. An isolated qualifying point is marked by a vertical line. Missing confidence limits break a highlighted range. The displayed confidence level follows `result$alpha`; no fixed p-value threshold is implied.

### Value

A ggplot object. Its data contains the selected curve; the `wsmmed_regions` attribute contains raw-unit grid interval endpoints. The `wsmmed_plot` attribute records engine, scale and confidence level.

### See Also

[plot\\_effects\(\)](#), [plot\\_conditional\\_effects\(\)](#), [plot\\_contrasts\(\)](#)

---

 PrepareData

---

*Prepare Data for Two-Condition Within-Subject Mediation (WsMed)*


---

### Description

`PrepareData()` transforms raw pre/post data into the set of variables required by the **WsMed** workflow. It handles *mediators*, *outcome*, *within-subject controls*, *between-subject controls*, *moderators*, and all necessary **interaction terms**, while automatically centering / dummy-coding variables as needed.

### Usage

```
PrepareData(
  data,
  M_C1,
  M_C2,
  Y_C1,
  Y_C2,
  C_C1 = NULL,
  C_C2 = NULL,
  C = NULL,
  C_type = NULL,
  W = NULL,
  W_type = NULL,
  center_W = TRUE,
  keep_W_raw = TRUE,
  keep_C_raw = TRUE
)
```

## Arguments

|                                     |                                                                                                                                          |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| <code>data</code>                   | A data frame with the raw pre/post measures.                                                                                             |
| <code>M_C1, M_C2</code>             | Character vectors: mediator names at occasion 1 and 2 (equal length).                                                                    |
| <code>Y_C1, Y_C2</code>             | Character scalars: outcome names at occasion 1 and 2.                                                                                    |
| <code>C_C1, C_C2</code>             | Optional character vectors: within-subject control names.                                                                                |
| <code>C</code>                      | Optional character vector: between-subject control names.                                                                                |
| <code>C_type</code>                 | Optional vector of the same length as C. Each element is one of "continuous", "categorical", or "auto" (default). Ignored when C = NULL. |
| <code>W</code>                      | Optional character vector: moderator names (one or more).                                                                                |
| <code>W_type</code>                 | Optional vector of the same length as W. Same coding as C_type. Ignored when W = NULL.                                                   |
| <code>center_W</code>               | Logical. Whether to center the moderator variable W.                                                                                     |
| <code>keep_W_raw, keep_C_raw</code> | Logical. If TRUE, keep the original W / C columns in the returned data.                                                                  |

## Details

The function performs the following steps:

1. Outcome difference:  $Y_{diff} = Y_{C2} - Y_{C1}$ .
2. Mediator variables for each pair ( $M_{C1}[i]$ ,  $M_{C2}[i]$ ):
  - $Mi_{diff} = M_{C2} - M_{C1}$
  - $Mi_{avg}$  is the mean-centered average of the two occasions.
3. Between-subject controls C:
  - Continuous variables are grand-mean centered ( $Cb1$ ,  $Cb2$ , ...).
  - Categorical variables (binary or multi-level) are expanded into  $k - 1$  dummy variables ( $Cb1\_1$ ,  $Cb2\_1$ ,  $Cb2\_2$ , ...), using the first level as the reference.
4. Within-subject controls Cw: difference and centered-average versions ( $Cw1_{diff}$ ,  $Cw1_{avg}$ , ...).
5. Moderators W (one or more):
  - Continuous variables are grand-mean centered ( $W1$ ,  $W2$ , ...).
  - Categorical variables are dummy-coded in the same way as C.
6. Interaction terms between each moderator column and each mediator column:
  - $int\_Mi\_diff\_Wj$ ,  $int\_Mi\_avg\_Wj$ .
7. Two attributes are added to the returned data:
  - "W\_info": raw names, dummy names, level mapping
  - "C\_info": same structure for between-subject controls.

Row counts are preserved even if input factors contain NA values (model.matrix is called with `na.action = na.pass`).

**Value**

A data frame containing at minimum:

- Ydiff
- Mi\_diff, Mi\_avg for each mediator
- centered or dummy-coded Cb\*, Cw\*diff, Cw\*avg
- centered or dummy-coded W\* and all int\_\* interaction terms

plus the attributes "W\_info" and "C\_info" described above.

**See Also**

[PrepareMissingData](#), [GenerateModelP](#), [wsMed](#)

**Examples**

```
set.seed(1)
raw <- data.frame(
  A1 = rnorm(50), A2 = rnorm(50), # mediator 1
  B1 = rnorm(50), B2 = rnorm(50), # mediator 2
  C1 = rnorm(50), C2 = rnorm(50), # outcome
  D1 = rnorm(50), D2 = rnorm(50), # within-subject control
  W_bin = sample(0:1, 50, TRUE), # between-subject binary C
  W_fac3 = factor(sample(c("Low", "Med", "High"), 50, TRUE)) # moderator W
)

prep <- PrepareData(
  data = raw,
  M_C1 = c("A1", "B1"), M_C2 = c("A2", "B2"),
  Y_C1 = "C1", Y_C2 = "C2",
  C_C1 = "D1", C_C2 = "D2",
  C = "W_bin", C_type = "categorical",
  W = "W_fac3", W_type = "categorical"
)
head(prep)
```

---

|                    |                                                                |
|--------------------|----------------------------------------------------------------|
| PrepareMissingData | <i>Prepare Data with Missing Values for Mediation Analysis</i> |
|--------------------|----------------------------------------------------------------|

---

**Description**

Handles missing values in the dataset through multiple imputation and prepares the imputed datasets for within-subject mediation analysis. The function imputes missing data, processes each imputed dataset, and provides diagnostics for the imputation process.

**Usage**

```

PrepareMissingData(
  data_missing,
  m = 5,
  method_num = "pmm",
  seed = 123,
  M_C1,
  M_C2,
  Y_C1,
  Y_C2,
  C_C1 = NULL,
  C_C2 = NULL,
  C = NULL,
  C_type = NULL,
  W = NULL,
  W_type = NULL,
  center_W = TRUE,
  keep_W_raw = TRUE,
  keep_C_raw = TRUE
)

```

**Arguments**

|                                     |                                                                                                                                                               |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>data_missing</code>           | A data frame containing the raw dataset with missing values.                                                                                                  |
| <code>m</code>                      | An integer specifying the number of imputations to perform. Default is 5.                                                                                     |
| <code>method_num</code>             | Character; imputation method for numeric variables (for example, "pmm", "norm"). Default is "pmm".                                                            |
| <code>seed</code>                   | An integer specifying the random seed for reproducibility. Default is 123.                                                                                    |
| <code>M_C1</code>                   | A character vector of column names representing mediators at condition 1.                                                                                     |
| <code>M_C2</code>                   | A character vector of column names representing mediators at condition 2. Must match the length of <code>M_C1</code> .                                        |
| <code>Y_C1</code>                   | A character string representing the column name of the outcome variable at condition 1.                                                                       |
| <code>Y_C2</code>                   | A character string representing the column name of the outcome variable at condition 2.                                                                       |
| <code>C_C1</code>                   | Character vector of within-subject control variable names (condition 1).                                                                                      |
| <code>C_C2</code>                   | Character vector of within-subject control variable names (condition 2).                                                                                      |
| <code>C</code>                      | Character vector of between-subject control variable names.                                                                                                   |
| <code>C_type</code>                 | Optional vector of the same length as <code>C</code> . Each element is "continuous", "categorical", or "auto" (default). Ignored when <code>C = NULL</code> . |
| <code>W</code>                      | Optional character vector: moderator names (at most J).                                                                                                       |
| <code>W_type</code>                 | Optional vector of the same length as <code>W</code> . Same coding as <code>C_type</code> . Ignored when <code>W = NULL</code> .                              |
| <code>center_W</code>               | Logical. Whether to center the moderator variable <code>W</code> .                                                                                            |
| <code>keep_W_raw, keep_C_raw</code> | Logical; keep the original <code>W / C</code> columns in the returned data?                                                                                   |

## Details

This function is designed to preprocess datasets with missing values for mediation analysis. It performs the following steps:

- Multiple imputation: Uses specified imputation methods (for example, predictive mean matching) to generate  $m$  imputed datasets.
- Data preparation: Applies [PrepareData](#) to each of the  $m$  imputed datasets to calculate difference scores and centered averages for mediators and the outcome variable.
- Imputation diagnostics: Provides summary diagnostics for the imputation process, including information about missing data patterns and convergence.

This function integrates imputation and data preparation, ensuring that the resulting datasets are ready for subsequent mediation analysis.

## Value

A list containing:

`processed_data_list` A list of  $m$  data frames, each representing an imputed and processed dataset ready for within-subject mediation analysis.

`imputation_summary` A summary of the imputation process, including diagnostics and convergence information.

## See Also

[PrepareData](#), [ImputeData](#), [wsMed](#)

## Examples

```
# Example dataset with missing values
data("example_data", package = "wsMed")
set.seed(123)
example_dataN <- mice::ampute(
  data = example_data,
  prop = 0.1
)$amp

# Prepare the dataset with multiple imputations
prepared_missing_data <- PrepareMissingData(
  data_missing = example_dataN,
  m = 5,
  M_C1 = c("A2", "B2"),
  M_C2 = c("A1", "B1"),
  Y_C1 = "C2",
  Y_C2 = "C1"
)

# Access processed datasets
processed_data_list <- prepared_missing_data$processed_data_list
imputation_summary <- prepared_missing_data$imputation_summary
```

---

print.wsMed

---

*Print Method for wsMed Objects*


---

## Description

Provides a comprehensive summary of results from a wsMed object, including:

- Input and computed variables with sample size.
- Model fit indices, regression paths, and variance estimates.
- Total, direct, and indirect effects with pairwise contrasts.
- Moderation effects and Monte Carlo confidence intervals for raw and standardized estimates (if applicable).
- Diagnostic notes for bootstrapping, imputation, and analysis parameters.

The output is formatted for clarity, ensuring an intuitive presentation of mediation analysis results, including dynamic confidence intervals, moderation keys, and C1-C2 coefficients.

## Usage

```
## S3 method for class 'wsMed'
print(x, digits = 3, ...)
```

## Arguments

|        |                                                                             |
|--------|-----------------------------------------------------------------------------|
| x      | A wsMed object containing the results of within-subject mediation analysis. |
| digits | Numeric. Number of digits to display in the results.                        |
| ...    | Additional arguments (not used currently).                                  |

## Details

This function is specifically designed to display results from the within-subject mediation analysis conducted using the wsMed function. Key features include:

- **Variables:**
  - Shows input variables (M\_C1, M\_C2, Y\_C1, Y\_C2) and computed variables like Ydiff, Mdiff, and Mavg.
  - Reports the sample size used in the analysis.
- **Model Fit Indices:**
  - Displays SEM fit indices (e.g., Chi-square, CFI, TLI, RMSEA, SRMR) to assess model quality.
- **Regression Paths and Variance Estimates:**
  - Summarizes path coefficients, intercepts, variances, and confidence intervals.
- **Effects:**
  - Reports total, direct, and indirect effects with their significance.

- Highlights pairwise contrasts between indirect effects for mediation paths.
- **Moderation Effects:**
  - Provides moderation results for identified variables with corresponding coefficients and paths.
- **Monte Carlo Confidence Intervals:**
  - Includes results for raw and standardized estimates obtained using methods such as MI or FIML.
- **Diagnostics:**
  - Summarizes analysis parameters like bootstrapping, imputation settings, Monte Carlo iterations, and random seeds.

### Value

Invisibly returns the input wsMed object for further use.

### See Also

[wsMed](#), [sem](#), [standardizedSolution\\_boot\\_ci](#)

### Examples

```
# Perform within-subject mediation analysis
data("example_data", package = "wsMed")
result1 <- wsMed(
  data = example_data,
  M_C1 = c("A1", "B1"),
  M_C2 = c("A2", "B2"),
  Y_C1 = "C1",
  Y_C2 = "C2",
  form = "P",
  Na = "FIML",
  standardized = FALSE,
  alpha = 0.05
)

# Print the results
print(result1)
```

---

printGM

---

*Print Formatted SEM Model Syntax*


---

### Description

Formats and prints the SEM model syntax generated by `GenerateModelCN`, `GenerateModelCP`, `GenerateModelP`, and `GenerateModelPC`. It organizes the equations into labeled sections for better readability.

**Usage**

```
printGM(x, ...)
```

**Arguments**

**x** A list or character string containing SEM model syntax. If **x** is a `wsMed()` result, it will extract and print the model syntax. If **x** is a `GenerateModel*`() result, it will format and print the model.

**...** Additional arguments (not used).

**Value**

Invisibly returns the formatted SEM model syntax.

**Examples**

```
data(example_data)
head(example_data)
prepared_data <- PrepareData(
  data = example_data,
  M_C1 = c("A1", "B1"),
  M_C2 = c("A2", "B2"),
  Y_C1 = "C1",
  Y_C2 = "C2"
)
sem_model <- GenerateModelPC(prepared_data)
printGM(sem_model)
```

---

```
standardize_moderation
```

*Standardize conditional mediation results using existing joint draws*

---

**Description**

Standardize conditional mediation results using existing joint draws

**Usage**

```
standardize_moderation(object)
```

**Arguments**

**object** A `wsMed` result with a moderator and stored MC or bootstrap draws.

Details

Conditional indirect and total effects are divided by the marginal model-implied SD of Ydiff. Conditional paths use their endpoint scales. Moderator probe values remain fixed in raw units; continuous interaction coefficients in mod\_coeff are reported per SD of W. Dummy variables retain 0/1 units. Coefficients and scales are transformed jointly for each draw. Intervals are percentile intervals, as in the raw conditional tables. Metadata attributes record scales, probe conventions and draw diagnostics. With fixed.x=TRUE, external moments are held fixed. MI uses pooled primitive parameters and the existing first-imputation probing reference.

Value

A moderation list with the same conditional tables and curves as the raw output, or a list with mc and boot components for ci\_method="both".

---

|       |                                                          |
|-------|----------------------------------------------------------|
| wsMed | <i>Within-Subject Mediation Analysis (Two-Condition)</i> |
|-------|----------------------------------------------------------|

---

Description

wsMed() fits a structural equation model (SEM) for two-condition within-subject mediation. It can handle missing data (DE, FIML, MI) and computes both unstandardized and standardized effects with bootstrap or Monte Carlo confidence intervals.

Usage

```
wsMed(  
  data,  
  M_C1,  
  M_C2,  
  Y_C1,  
  Y_C2,  
  C_C1 = NULL,  
  C_C2 = NULL,  
  C = NULL,  
  C_type = NULL,  
  W = NULL,  
  W_type = NULL,  
  MP = NULL,  
  form = c("P", "CN", "CP", "PC", "UD"),  
  Na = c("DE", "FIML", "MI"),  
  alpha = 0.05,  
  mi_args = list(),  
  R = 20000L,  
  bootstrap = 2000,  
  boot_ci_type = "perc",  
  iseed = 123,  
  fixed.x = FALSE,
```

```

ci_method = c("mc", "bootstrap", "both"),
MCmethod = NULL,
seed = 123,
standardized = FALSE,
verbose = FALSE,
paths = NULL
)

```

## Arguments

|              |                                                                                                                                                                                                                                                                                                                                                                      |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| data         | A <a href="#">data.frame</a> containing the raw scores.                                                                                                                                                                                                                                                                                                              |
| M_C1, M_C2   | Character vectors of mediator names under condition 1 and 2.                                                                                                                                                                                                                                                                                                         |
| Y_C1, Y_C2   | Character scalars for the outcome under each condition.                                                                                                                                                                                                                                                                                                              |
| C_C1, C_C2   | Character vectors of within-subject covariates (per condition).                                                                                                                                                                                                                                                                                                      |
| C            | Character vector of between-subject covariates.                                                                                                                                                                                                                                                                                                                      |
| C_type       | Character; type of C: "continuous" or "categorical".                                                                                                                                                                                                                                                                                                                 |
| W            | Character vector of moderators. Default NULL.                                                                                                                                                                                                                                                                                                                        |
| W_type       | Character; "continuous" or "categorical".                                                                                                                                                                                                                                                                                                                            |
| MP           | Character vector identifying which regression paths are moderated (for example, "a1", "b_1_2", "cp"). Main effects of W already included in each regression are always used when computing conditional intercepts, whether or not a/cp is explicitly listed in MP.                                                                                                   |
| form         | Model type: "P", "CN", "CP", "PC", or "UD". Use "UD" to specify a user-defined mediation model. Values are case-insensitive.                                                                                                                                                                                                                                         |
| Na           | Missing-data method: "DE", "FIML", or "MI". Values are case-insensitive.                                                                                                                                                                                                                                                                                             |
| alpha        | Numeric vector in (0, 1); two-sided significance levels.                                                                                                                                                                                                                                                                                                             |
| mi_args      | List of MI-specific controls: <ul style="list-style-type: none"> <li>m Number of imputations. Default 5.</li> <li>method_num Imputation method for mice().</li> <li>decomposition Covariance-decomposition method ("eigen", "chol", "svd").</li> <li>pd Logical; positive-definiteness check.</li> <li>tol Tolerance for the positive-definiteness check.</li> </ul> |
| R            | Integer; number of Monte Carlo draws. Default 20000L.                                                                                                                                                                                                                                                                                                                |
| bootstrap    | Integer; number of bootstrap replicates (DE and FIML only).                                                                                                                                                                                                                                                                                                          |
| boot_ci_type | Character; bootstrap CI type: "perc", "bc", or "bca.simple".                                                                                                                                                                                                                                                                                                         |
| iseed, seed  | Integer seeds for bootstrap and Monte Carlo, respectively.                                                                                                                                                                                                                                                                                                           |
| fixed.x      | Logical; passed to <b>lavaan</b> .                                                                                                                                                                                                                                                                                                                                   |
| ci_method    | CI engine: "mc", "bootstrap", or "both". Values are case-insensitive. The default (also used for NULL) is "mc". With Na = "MI", only "mc" is supported.                                                                                                                                                                                                              |
| MCmethod     | If Na = "FIML" and ci_method = "mc", choose "mc" (default) or "bootSD".                                                                                                                                                                                                                                                                                              |

|              |                                                                                                                                                                                                                                                           |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| standardized | Logical; if TRUE, return standardized parameter tables (including defined effects at the reference moderator value). Raw conditional results remain in moderation; standardized conditional tables and curves are added in moderation_std. Default FALSE. |
| verbose      | Logical; print progress messages.                                                                                                                                                                                                                         |
| paths        | A character vector defining directed paths when form = "UD". Paths are specified using mediator labels M1, M2, and so on, with Y denoting the outcome. For example, c("M1 -> M3", "M3 -> Y", "M2 -> Y"). Must be NULL for the predefined model forms.     |

## Details

Model structures:

- "P": parallel mediation
- "CN": chained (serial) mediation
- "CP": chained then parallel
- "PC": parallel then chained
- "UD": user-defined mediation model

Missing-data strategies:

- "DE": list-wise deletion
- "FIML": full-information maximum likelihood
- "MI": multiple imputation via **mice**

Confidence-interval engines:

- Bootstrap: percentile, BC, or BCa (DE and FIML only)
- Monte Carlo: draws via **semmeci** (all Na options)

For Na = "FIML", you may choose MCmethod = "mc" (default) or "bootSD" to add a finite-sample SD correction.

Standardization divides differences by their marginal model-implied SDs, without recentering them. Dummy variables retain 0/1 units; interaction terms use the product of their component scale factors, not the interaction column SD. MC and bootstrap draws are transformed jointly with their scales. Standardized bootstrap intervals use type-7 quantiles; bc and bca.simple apply bias correction with zero acceleration. P-values use inversion of that distribution and require at least 1000 valid replicates.

Conditional tables use percentile intervals and fixed numerical probes. With fixed.x=TRUE, scale transformations condition on the fitted external moments rather than adding sampling uncertainty for those moments. In MI, probes/centering references use the first completed data set; fixed.x=TRUE also conditions on its external moments in the pooled transform. No new population-relative probing or imputation method is implemented here.

Workflow: (1) preprocess -> (2) generate SEM syntax -> (3) fit -> (4) compute confidence intervals -> (5) optional: standardize estimates.

**Value**

An object of class "wsMed" with elements:

**data** Preprocessed data frame.

**sem\_model** Generated **lavaan** syntax.

**mc** List with Monte Carlo draws, bootstrap tables (if any), and the fitted model.

**moderation** Raw conditional or moderated effect tables.

**moderation\_std** Standardized conditional tables and curves when standardized=TRUE and a moderator is supplied.

**form,Na,alpha** Analysis settings.

**paths** The user-defined paths when form = "UD"; otherwise NULL.

**input\_vars** Names of all user-supplied variables.

**Examples**

```
data("example_data", package = "wsMed")
set.seed(123)
result <- wsMed(
  data = example_data,
  M_C1 = c("A2", "B2"),
  M_C2 = c("A1", "B1"),
  Y_C1 = "C1", Y_C2 = "C2",
  form = "P", Na = "DE"
)
print(result)
```

# Index

`data.frame`, [28](#)

`GenerateModelCN`, [2](#)

`GenerateModelCN()`, [5](#), [8](#), [10](#)

`GenerateModelCP`, [4](#)

`GenerateModelCustom`, [6](#)

`GenerateModelP`, [7](#), [21](#)

`GenerateModelP()`, [3](#), [5](#), [10](#)

`GenerateModelPC`, [8](#)

`ggplot2::ggsave()`, [17](#)

`ImputeData`, [10](#), [23](#)

`MCMl2`, [11](#)

`plot_conditional_effects`, [13](#)

`plot_conditional_effects()`, [16](#), [17](#), [19](#)

`plot_contrasts`, [15](#)

`plot_contrasts()`, [15](#), [17](#), [19](#)

`plot_effects`, [16](#)

`plot_effects()`, [15](#), [16](#), [19](#)

`plot_moderation_curve`, [18](#)

`plot_moderation_curve()`, [17](#)

`PrepareData`, [19](#), [23](#)

`PrepareData()`, [3–5](#), [7–10](#)

`PrepareMissingData`, [21](#), [21](#)

`print.wsMed`, [24](#)

`printGM`, [25](#)

`sem`, [25](#)

`standardize_moderation`, [26](#)

`standardizedSolution_boot_ci`, [25](#)

`wsMed`, [21](#), [23](#), [25](#), [27](#)

`wsMed()`, [3](#), [5](#), [8](#), [10](#), [14](#), [15](#), [17](#), [18](#)